

INNOVATIVE 2 BOTTLE REFRIGERATED PROFESSIONAL SYSTEM WITH ENOMATIC® TECHNOLOGY

ELEGANT DESIGN, COMPACTNESS AND EASY INSTALLATION (PLUG & PLAY)

PERFECT ALSO FOR HOME USE


OPTION OF CONNECTING MULTIPLE SYSTEMS IN A LINE (MODULARITY)



eno one

- **Available model:** eno one 2/r (2 bottles in a line)
- **Wine storage temperature:** 6°C - 18°C (43°F - 64°F)
- **Installation:** "plug & play"
- **Gas supply:**
Nitrogen E941 or Argon E938
(disposable or external cylinder; not included)
- **Volumes:** 1 free, 1 or 3 programmable
- **Materials:** stainless steel and black Gepax®
- **Lighting system:** LED lighting with adjustable intensity
- **Bottle positioning system:** self-centering lifted by pistons with gas spring
- **Refrigeration system:** with thermo-electric module
- **Dispenser settings:** via central touch-display
- **Maintenance:** light signal for tap cleaning
- **Optional accessories:**
 - Extra side panel set (white or black color)
 - Connection kit
 - Spacer for short bottles
 - Gas canister cover
 - Dividing panel to separate bottles, 1 for white wines and 1 for red wines
 - Cylinder and pressure regulator: disposable argon canister (E938) 0,950lt - 32,12fl oz (sufficient for approx. 80 bottles)

Note: The image shows the model with extra side panels (white)



model	W	H	D	Weight	Electrical system requirements
eno one 2/r	27,6 cm 10,88 inch	59,7 cm 23,49 inch	35,1 cm 13,82 inch	12 kg	100-240 V 50-60 Hz 70 W (based on market destination)